OCT 6 1980

Occupational Safety and Health Administration

MATERIAL SAFETY DATA SHEET

2122-2672

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

., SECT	TION I
MANUFACTURER'S NAME FRANKLIN OIL CORP. (OHIO)	EMERGENCY TELEPHONE NO. 216/232-3000
ADDRESS (Number, Street, City, State, and ZIP Code) 40 SOUTH PARK STREET, BEDFORD, OHIO 44146	
CHEMICAL NAME AND SYNONYMS	RUST FOIL 652-2
CHEMICAL FAMILY	FORMULA

SECTION	J 11 -	HAZAF	RDOUS INGREDIENTS		
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS		_			
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES			%	TLV (Units)	
1					

N.D.	SPECIFIC GRAVITY (H ₂ O=1) PERCENT, VOLATILE	0.90
· 1	PERCENT VOLATILE	
7	BY VOLUME (%)	WIL.
1	EVAPORATION RATE (_Ether =1)	∠ 1
NEG.		
	NEG.	1 EVAPORATION RATE (_Ether=1)

SECTION IV - FIRE AND E	XPLOSION HAZARD DAT	A	:
FLASH POINT (Method used) 400°F. COC	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA FOAM, CO, DRY CHEMICAL	· ·		
SPECIAL FIRE FIGHTING PROCEDURES			
FIGHT AS A CLASS B FIRE	Z.		
UNUSUAL FIRE AND EXPLOSION HAZAROS			

PAGE (1)

(Continued on reverse side)

Form OSHA-20 Rev. May 72

. م	OCT 6 1980 S	EUTION	1 V - H	EΑ	LTH HAZARD DATA			
THRESHOLD LIMIT	TVALUE							
EFFECTS OF OVER	REXPOSURE							
	C.0.C.C.C.C.C.C.C.C.C.C.C.C.C.C.C.C.C.C	10.55						
FLI	JSH SKIN OR EY	ES WITH	H WATER	₹.	IF INGESTED, DO NOT INDUCE	VOMITING, SEE A		
PHY	YSICIAN.							

		SECTIO	- IV NC	- R	EACTIVITY DATA			
STABILITY	UNSTABLE		CONDIT	101	IS TO AVOID			
	STABLE	Х	4	•				
	(Materials to avoid)		NG OXI	DIZ	ING AGENTS.			
UPON COMBUST	MPOSITION PRODU ION:	CTS CO,	, co,		Leavent to avoic			
HAZARDOUS POLYMERIZATION	MAY OCCU	R			CONDITIONS TO AVOID			
POCTMERIZATION	WILL NOT	OCCUR	X	· -				
			·					
	SECT	ION VI	I - SPIL	LL	OR LEAK PROCEDURES	· · · · · · · · · · · · · · · · · · ·		
STEPS TO BE TAKE	N IN CASE MATERI							
CLEAN UP WITH	OIL ABSORBEN	r mater	RIAL.					
			,					
WASTE DISPOSAL N	METHOD							
DISPOSE OF IN	AUTHORIZED LA	ANDFILL	•					
		· · · · · · · · · · · · · · · · · · ·	·					
	SECTION	VIII - S	SPECIAL	L P	ROTECTION INFORMATION			
RESPIRATORY PRO	TECTION (Specify ty					5		
VENTILATION	LOCAL EXHAUST				SPECIAL			
	MECHANICAL /Ger	MECHANICAL (General)			OTHER	OTHER		
PROTECTIVE GLOV	es NEOPRENE				EYE PROTECTION SAFETY GLASSES OR COGGLES	,		
OTHER PROTECTIV								
					CIAL PRECAUTIONS			
RECAUTIONS TO E	BE TAKEN IN HAND	LING AND	SIOKIN					
THER PRECAUTIO	NS							
								
AGE (2)					R. E. ICO. A	Form OSHA-20 Rev. May 72		

68010

R. E. Klotz, Technical Director K. E. World